



PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: POST

Examiner: T. MAYO

Serial No.: 10/649,153

Group Art Unit: 3671

Conf No.: 5019

Docket No.: 1810US01-EE

Filed: August 27, 2003

Title: RESCUE UNDERLAY FOR MATTRESSES

Marked Up Copy of Substitute Specification

Rescue underlay for mattresses

FIELD OF THE INVENTION

The invention relates to a rescue underlay for mattresses with the features of the introductory part of claim 1.

5

BACKGROUND

Rescue underlays for mattresses of the usual kind have a double function. On the one hand such a rescue underlay is, by its underlay mat, a mattress protective cover for pressure relief of the mattress at the underside. On the other hand, the rescue underlay serves in the event of a catastrophe for rapid evacuation of a reclining patient. This applies to hospitals, homes for the elderly, nursing wards, etc.

Rescue underlays of the usual kind are, as a precaution, kept in hand under mattresses in order in the case of a catastrophe to fix the reclining patient on the mattress to be lying down and to then be able to pull the mattress on the rescue underlay over the ground. A single person can then rescue a patient, whereas in the case of use of stretchers or the like at least two persons are required per rescued person.

The rescue underlay from which the invention proceeds (DE 88 14 414 U1) comprises an underlay mat of a reticular or gridlike woven fabric of plastic, to which a pull loop of a plastic woven fabric strip for pulling the underlay mat inclusive of mattress and patient is attached at one end. Patient securing belts, which have connecting elements at both ends for closing the patient securing belts, are attached to the longitudinal sides of the underlay mat. In the case of the previously explained prior art these connecting elements are simple loops; other prior art mentions ~~Velcro~~ VELCRO hook and loop connections (US 4 124 908 A) and quick-action clamping locks or quick release buckles (GB 1 434 832 A).

The known rescue underlays have already proved themselves in the respect that a patient lying on the mattress and secured and held by the patient securing belts under his cover can be drawn in problem-free manner over the ground by a helper by means of

30

the pull loops. Even pulling in stairwells has proved possible, so that such a rescue underlay in fact offers a considerable advantage in emergency situations.

5 It is already known to provide a rescue underlay of the conventional kind with additional, cushioning support wedges, particularly at the head end, at the foot end and in the middle region, which are arranged under the mattress and are to prevent slipping of the patient on the mattress (WO 00/74785 A1).

10 It has proved that the known rescue underlays for mattresses still present a need for improvement in handling.

SUMMARY OF THE INVENTION

15 The teaching of the present invention solves the previously outlined problem, in the case of a rescue underlay for mattresses with the features of the introductory part of claim 1, by the features of the characterising part of claim 1.

20 According to the invention the plastic flat material, which forms the rectangular underlay mat, is not simply a plastic woven fabric or plastic net material, but a flat material providing a spring travel. In other words, the underlay mat as such consists of a plastic material which itself has a certain cushioning function, because this material as such provides a spring travel, even if relatively small overall by comparison with the mattress. The spring constant of the plastic flat material will usually be substantially greater than the spring constant of the mattress itself. The underlay mat thus forms a relatively hard spring, where against the mattress forms a softer spring. This combination has
25 proved to be advantageous for the transport problem present here.

Various materials can be used as plastic flat material providing a spring travel. Use can obviously be made of foam materials, air-bubble films or plastic materials which find use in foam mattresses. In that case, however, of particular significance is the fact that
30 the requisite tensile strength has to be achieved in longitudinal direction of the underlay

mat. Further, certain safety features must be achieved like e.g. flame-resistance or the like.

Of particular significance, therefore, is a preferred embodiment of the rescue underlay
5 according to the invention which is characterised in that the plastic flat material providing a spring travel is a spacer woven fabric or, in particular, a spacer knitted fabric. A spacer woven fabric is a material which has two fabric cover layers which are held at a spacing of a few millimetres by distance-maintaining bridge threads (information from the company Haufler Industrievertretungen ~~under www.haufler-~~
10 ~~iv.de/abstandsgewebe.htm~~). Spacer knitted fabrics have textile outer surfaces of greater width of stitch link, the outer surfaces being connected by spacer threads and held at the desired distance. The spring characteristic of a spacer woven fabric or a spacer knitted fabric results from the spacer threads or bridge threads (data from Textilinstitut Greiz ~~under www.titv-greiz.de/deulagwirker.htm~~).

15 Further preferred refinements and developments moreover form the subject of further subclaims.

~~Claim 10~~ One embodiment relates to a specific way to secure the patient securing belts
20 to the rescue underlay when they are not in use in a way enabling tearing off of the free ends if necessary.

~~Claim 11~~ Another embodiment, also a separate invention relating to the rescue underlay
for mattresses, relates to a particular way to accommodate the patient securing belts
25 when not in use. This is done in tunnel-like receptions preferably on the underside of the underlay mat as explained in this claim. Further subclaims related to this claim describe refinements.

Finally, it is explained that it is possible to permanently attach such rescue underlay to a
30 mattress or even integrate a rescue underlay into a mattress. So part of the invention is a complete rescue mattress integrating the describe rescue underlay as well.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention is explained in more detail in the following by reference to a drawing illustrating merely a preferred example of embodiment. In the drawing

5

Fig. 1 shows, in a perspective illustration, a rescue underlay for a mattress, which is here illustrated with a patient lying thereon,

10

Fig. 2 shows an embodiment of a rescue underlay according to the invention,

Fig. 3 shows a head region of a rescue underlay according to Fig. 2,

15

Fig. 4a and ~~shows~~ show a spacer knitted fabric as is preferably used as flat material providing a spring travel, in section,

Fig. 5 shows a second embodiment of a rescue underlay according to the invention in a plan view,

20

Fig. 6 shows a third embodiment in that a mattress with a rescue underlay according to the invention permanently affixed to it or integrated into it.

DETAILED DESCRIPTION OF THE INVENTION

25 The subject of the invention is a rescue underlay for mattresses as has been described in the general part of the description.

Fig. 1 shows a mattress 1 on which a patient 3, covered by a cover 2, lies. Disposed under the mattress 1 is a rescue underlay with a rectangular underlay mat 4 consisting of a plastic flat material which has a high tensile strength and is preferably substantially
30 tear-proof. The underlay mat 4 has approximately the dimensions of the mattress 1. Obviously it is possible in principle for the underlay mat 4 to be somewhat larger or

somewhat smaller, particularly somewhat longer or somewhat shorter, than the mattress 1. However, it could also be imagined that there are different underlay mats 4 adapted to respectively differently sized mattresses 1.

5 Since in the field of hospitals, homes for the elderly and nursing homes the dimensions of mattresses 1 are largely uniform, it is usually possible to manage with an underlay mat 4 of a specific format.

10 The underlay mat 4 serves, for the mattress 1, initially as a mattress protective cover. To that extent the underlay mat 4 has a classic function. Beyond that, this underlay mat 4 also serves as a rescue means in emergency, as has been described in the general part of the description. For that purpose the rescue underlay is provided with pull loops 5, patient securing belts 6 and mattress retaining bands 7 attached to the underlay mat 4 (Fig. 2). The pull loops 5 are disposed directly adjacent to one another at the edge of the underlay mat 4 at both ends, so that the underlay mat 4 can be pulled in problem-free
15 manner in both directions. The orientation of the underlay mat 4 under the mattress 1 thus does not matter.

20 Other pull aids, for example longer hand loops such as shown in US 5 150 487 A, can also be used instead of pull loops 5.

The patient securing belts 6 can also be arranged and connected in different mode and manner, the prior art showing a plurality of possibilities to which reference has already been made above.

25 Finally, it is recommended to also connect the underlay mat 4 of the rescue underlay in whatever manner to the mattress 1 itself. The illustrated mattress retaining bands 7 arranged at an angle in the corners correspond with that also realised in the state of the art from which the invention proceeds. Other prior art techniques show ~~Velcro~~ VELCRO
30 hook and loop bands or additional belts.

Figs. 2 and 3 show the rescue underlay according to the invention in enlarged illustration and without mattress 1. [[Fig. 4 permits]] Figs. 4a and 4b permit recognition of a section through the utilised plastic flat material of the underlay mat 4. To that extent the teaching of the invention is now to the effect that the plastic flat material of the underlay mat 4 is a flat material providing a spring travel. The advantages of a flat material, which itself provides a spring travel, as underlay mat 4 reside in the fact that an additional spring travel is provided, thus an additional cushioning takes place which is felt to be very comfortable by the transported persons in the case of transport.

A number of alternatives have been mentioned in the general part of the description for the plastic flat material providing a spring travel. In particular, sponge materials, air-bubble films or plastic materials such as used for foam mattresses come to mind for this purpose. However, with consideration of the requisite high tensile strength of the plastic flat material the illustrated, preferred form of embodiment of the rescue underlay according to the invention exhibits, as plastic flat material, a spacer woven fabric or a spacer knitted fabric. Spacer woven fabrics and spacer knitted fabrics are known as such from the state of the art. Their use is of particular advantage in the illustrated rescue underlay. Reference may be made to the cited references mentioned in the general part of the description with regard to spacer woven fabrics and spacer knitted fabrics.

It is recommended, for the present purpose of use, that the spacer woven fabric or spacer knitted fabric has a thickness of 4 mm to 20 mm, preferably approximately 6 mm to approximately 14 mm, especially of 6 mm or of 10 mm or of 14 mm. With regard to a spacer woven fabric of 6 mm, reference may be made to a technical data sheet of Müller-Textil GmbH, Industriestrasse 8, 51674 Wiehl, for the article 5754-0600 with a thickness of 6.0 mm or for the article 5556-1000 for a material of the thickness of 10.0 mm.

Spacer knitted fabrics of Müller Textil GmbH have, for example, the technical data sheet for the article 5900-1000 for a material with 10 mm thickness. In general, refer-

ence may be made here to the web page of the company Müller Textil GmbH under
~~www.muellertextil.de.~~

Spacer knitted fabrics and spacer woven fabrics have become known, in particular,
5 from polyester material. Polyester is also a selection of interest for other plastic materi-
als which provide a spring travel.

Moreover, for the definition of the plastic flat material for the underlay mat 4 a flame-
resistant or even fire-proof material is preferred. Moreover, it is considered an advan-
10 tage that a non-decaying material is used. It is advisable that the material should not be
hygroscopic, in order to keep the mattress dry. This is an advantage for cleaning of the
rescue underlay, too. Apart from the above mentioned polyester material a polyamide
fiber material, in particular an aramide fiber material (trade name Kevlar), a glass fiber
material or a saran fiber material is a reasonable choice (the description of the different
15 materials can be found in RÖMPP "Chemie", 10. edition 1996-1999, Georg Thieme
Verlag Stuttgart, New York.

The embodiment illustrated in [[Fig. 4]] Figs. 4a and 4b moreover ~~shows~~ show that in
accordance with preferred teaching of the invention the flat material providing a spring
20 travel, in particular the spacer woven fabric or spacer knitted fabric, has at the underside
a closed plastic film coating 8 preferably of polyurethane material or polyester material,
which has a low sliding friction, preferably a lower sliding friction than the plastic flat
material itself. In Fig. 4a) this coating is illustrated at the top and Fig. 4b) shows the
normal cover layer at the top. In the illustrated embodiment there is provided a polyure-
25thane coating which is sealed, non-water-permeable, washable and readily capable of
being disinfected as well as preferably, air-permeable. The sliding friction of such a
coating is so low that the rescue underlay can be easily pulled over smooth floor cover-
ings. This facilitates transport of the patient by rescue personnel.

30 Different demands are imposed on the slidability of the rescue underlay. On a flat path,
the lowest possible sliding friction shall be present. However, this can lead to the con-

sequence that on a sloping path or on stairs the rescue underlay can slip too quickly, which prejudices handling of the rescue underlay by the rescuer. According to a further and preferred teaching which is indicated in connection with Fig. 2, it can be provided that the plastic flat material has on the underside, especially on the film coating 8, at least an area with higher sliding friction which can as a braking surface 9. In the illustrated and preferred embodiment it is provided that the braking surface 9 is arranged in at least one end region of the underlay mat 4. Preferably a braking surface 9 is arranged at the underside of the underlay mat 4 in each end region of the underlay mat 4, particularly on the film coating 8.

The arrangement of the braking surface 9 at the indicated locations is based on the recognition that an end region of the underlay mat 4 during pulling of the rescue underlay by a rescuer is inevitably raised from the ground. The braking surface 9 here is ineffective. The other end region of the underlay mat 4 is less strongly loaded than the middle region of the underlay mat 4, because in the other end region either the head or the feet of the patient 3 is or are disposed according to the respective position of the patient 3. The heavier middle region of the patient 3, which ensures high friction by high force of pressing on the ground, is disposed therebetween. By raising the rescue underlay together with the mattress 1 and the patient 3 a rescuer on the stairs or on a sloping piece of ground can more strongly load the braking surface 9 at the opposite end in intended manner so that the braking effect increases. In particular, this is more or less automatically the case on stairs.

Fig. 3 moreover shows that in the illustrated example of embodiment it is further provided that an additional layer 10 of a flat material providing a spring travel, particularly a spacer woven fabric or a spacer knitted fabric, is fixedly attached, in particular sewn, glued and/or welded, to the underlay mat 4, preferably at the underside in an end region. The additional layer 10 of a flat material providing a spring travel is, in particular, similarly a spacer woven fabric or spacer knitted fabric, preferably such with a somewhat greater thickness.

Figs. 2 and 3 of the drawing allow particularly clear recognition that the illustrated rescue underlay is also particularly advantageously designed with respect to the furnishing of the patient securing belt 6 in the rest state. This is a different and independent advantage of the present rescue underlay. It is provided, in particular, that the patient securing
5 belts 6 are placed at the edge of the underlay mat 4 and connected at the free ends thereof with the material of the underlay mat 4 by stitching or by means of ~~Velcro~~ VELCRO hook and loop connections in a way enabling tearing off of the free ends if necessary. At the ends of the closure elements 11 the patient securing belts 6 are here fastened to the underlay mat 4 by a few stitches. Thus, the patient securing belts 6 are
10 normally accommodated in virtually invisible manner under the mattress 1, but nevertheless can be quickly separated at the ends by tearing off from the underlay mat 4 in order to fix the patient 3.

Fig. 5 shows an embodiment of the rescue underlay with an underlay mat 4 providing in
15 addition to the pull loops 5 at the edge of the underlay mat 4 a longer end pull loop 5' at the head end. Fig. 5 shows the hand pull loop 5' extended and, in dashed lines, in its non-used position. In this position it is inserted between the pull loops 5 under the underlay mat 4. By means of the extended hand pull loop 5' the head end underlay mat 4 can be managed by a rescuer for example when transporting a patient downstairs, without
20 the rescuer necessarily bending to much.

Pull loops 5 should have a sufficient gripping width so that a rescuer with thick safety gloves can easily grip the pull loops 5.

25 Safety regulations in particular in Germany explain that safety relevant parts, in particular the closure elements 11 of the quick action and quick release buckles for the patient securing belts 6 should preferably be in blue colour.

The embodiment shown in Fig. 5 has a particular design in that the underlay mat 4,
30 preferably on its underside is provided with tunnel-like receptions 12 accommodating the patient securing belts 6, wherein the patient securing belts 6 when not in use are po-

sitioned within the tunnel-like receptions 12 lengthwise, wherein one end of the respective patient securing belt 12, in particular a closure element 11 at the end of the patient securing belt 12, is protruding from the tunnel-like reception 12 such that it can be easily located and gripped in a rescue situation.

5

In this embodiment it is provided that the tunnel-like receptions 12 are positioned substantially transversely to the underlay mat 4. The embodiment shows that one tunnel-like reception 12 houses both parts of the patient securing belt 6. In a rescue situation the parts can be drawn from the tunnel-like reception 12 in opposite directions so that the closure elements 11 on the ends of the parts can be connected to secure the patient 3 on the mattress 1. However, an alternative is to house each part of a patient securing belt 6 in its own tunnel-like reception 12.

10
15 Further it is provided here that the tunnel-like receptions 12 are connected to the underlay mat 4 by sewing, in particular to the underside thereof. In the case that an additional layer is positioned on the underside of the plastic flat material to form a plastic film coating 8 it may be an option to use this plastic film coating 8 to form the tunnel-like receptions 12 on the underside of the underlay mat 4 by means of respective darts.

20 The embodiment of Fig. 5 discloses the quick connecting systems as closure elements 11 on the patient securing belts 6.

25 The embodiment of Fig. 5 further discloses that here the rescue underlay comprises altogether three patient securing belts 6 positioned in different distances from the head end of the underlay mat 4, wherein those distances preferably are about 50 cm, about 80 cm and about 120 cm.

30 In Fig. 5 the pull loops 5 are shown to be attached to the underlay mat 4 from the upper side. Of course, they can be attached to the underlay mat 4 from the underside as well if this is to be preferred from a handling standpoint. Such option is disclosed in Fig. 1.

Finally, there is provided a mattress characterised in that a rescue underlay, preferably according to any one of the claims 1 to 14 is permanently affixed to the mattress or is integrated into the mattress. This is then a kind of "rescue mattress" as such. This is indicated with the integrated mattress shown in Fig. 6.

WHAT IS CLAIMED IS:

Claims:

1. Rescue underlay for mattresses (1), comprising
a substantially rectangular underlay mat (4) consisting of a plastic flat material which
5 has a high tensile strength, the dimensions of which approximately correspond with the
dimensions of the mattress (1),
pull loops (5) or the like, patient securing belts (6) and, optionally, mattress retaining
bands (7) or the like, all attached to the underlay mat (4),
characterised in that
10 the plastic flat material of the underlay mat (4) is a flat material that itself is providing a
spring travel.
2. Rescue underlay according to claim 1, characterised in that the plastic flat material
is a spacer woven fabric or, in particular, a spacer knitted fabric.
- 15 3. Rescue underlay according to claim 2, characterised in that the spacer woven fabric
or spacer knitted fabric has a thickness of 4 mm to 20 mm, preferably of approximately
6 mm to approximately 14 mm, particularly of 6 mm or of 10 mm or of 14 mm.
- 20 4. Rescue underlay according to any one of the claims 1 to 3, characterised in that the
plastic flat material is a flame-resistant or fire-proof material and/or a non-decaying ma-
terial and/or a non-hygroscopic material and/or polyester material, polyamide fiber ma-
terial, in particular aramide fiber material, glass fiber material or saran fiber material.
- 25 5. Rescue underlay according to any one of the claims 1 to 4, characterised in that the
plastic flat material, particularly the spacer woven fabric or spacer knitted fabric, has at
the underside a closed plastic film coating (8), preferably of polyurethane material or of
polyester material which has a low sliding friction, preferably a lower sliding friction
than the plastic flat material itself.

6. Rescue underlay according to claim 5, characterised in that the film coating (8) is water-impermeable, washable and readily able to be disinfected as well as, preferably, air-permeable.

5 7. Rescue underlay according to any one of the claims 1 to 6, characterised in that the plastic flat material has on the underside, particularly on the film coating (8), at least one area with higher sliding friction which optionally acts as a braking surface (9).

8. Rescue underlay according to claim 7, characterised in that the braking surface (9)
10 is arranged in at least one end region of the underlay mat (4).

9. Rescue underlay according to any one of the claims 1 to 8, characterised in that an additional layer (10) of a plastic flat material providing a spring travel, particularly a spacer woven fabric or a spacer knitted fabric, is fixedly attached, particularly sewn,
15 glued and/or welded, to the underlay mat (4), preferably at the underside, in an end region thereof.

10. Rescue underlay for mattresses (1), comprising
a substantially rectangular underlay mat (4) consisting of a plastic flat material which
20 has a high tensile strength, the dimensions of which approximately correspond with the dimensions of the mattress (1),
pull loops (5) or the like, patient securing belts (6) and, optionally, mattress retaining bands (7) or the like, all attached to the underlay mat (4),
particularly according to any one of the claims 1 to 9,
25 **characterised in that**
the patient securing belts (6) are placed at the edge of the underlay mat (4) and are connected at the free ends thereof with the material of the underlay mat (4) by sewing or by means of ~~Velcro~~ VELCRO hook and loop connections in a way enabling tearing off of the free ends if necessary.

30

11. Rescue underlay for mattresses (1), comprising

a substantially rectangular underlay mat (4) consisting of a plastic flat material which has a high tensile strength, the dimensions of which approximately correspond with the dimensions of the mattress (1),

5 pull loops (5) or the like, patient securing belts (6) and, optionally, mattress retaining bands (7) or the like, all attached to the underlay mat (4),

particularly according to any one of the claims 1 to 9,

characterised in that

10 the underlay mat (4), preferably on its underside, is provided with tunnel-like receptions (12) accommodating the patient securing belts (6), wherein the patient securing belts (6) when not in use are positioned within the tunnel-like receptions (12) lengthwise, wherein one end of the respective patient securing belt (12), in particular a closure element (11) at the end of the patient securing belt (12), is protruding from the tunnel-like reception (12) such that it can be easily located and gripped in a rescue situation.

15 12. Rescue underlay according to claim 11, characterised in that the tunnel-like receptions (12) are positioned substantially transversely to the underlay mat (4).

20 13. Rescue underlay according to claim 11 or claim 12, characterised in that the tunnel-like receptions (12) are connected to the underlay mat (4) by sewing, in particular to the underside thereof.

25 14. Rescue underlay according to any one of the claims 1 to 13, characterised in that the rescue underlay comprises altogether three patient securing belts (6) positioned in different distances from the head end of the underlay mat (4), wherein those distances preferably are about 50 cm, about 80 cm and about 120 cm.

30 15. Mattress characterised in that a rescue underlay, preferably a rescue underlay according to any one of the claims 1 to 14, is permanently affixed to the mattress or is integrated into the mattress.

ABSTRACT

Abstract:

5 ~~Disclosed is a~~ A rescue underlay for mattresses (1), comprising a substantially rectan-
gular underlay mat (4) consisting of a plastic flat material which has a high tensile
strength, the dimensions of which approximately correspond with the dimensions of the
mattress (1), pull loops (5) or the like, patient securing belts (6) and, optionally, mat-
tress retaining bands (7) or the like, all attached to the underlay mat (4). This particular
rescue underlay has an underlay mat 4 which has a flat material that itself is providing a
10 spring travel. In a preferred embodiment the plastic flat material of the underlay mat 4
is a spacer woven fabric or, in particular, a spacer knitted fabric. A mattress can be
separately combined with such rescue underlay or can even be integrated with a rescue
underlay to form a rescue mattress.

15

(Fig. 5)